

Safety Data Sheet
According to the (US) Hazard Communication Standard (29 CFR 1910.1200)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name	Sudan Black B (IV), 0.3% in 60% Ethanol	
NCL Catalog Number	S-99X	
Product Description	Laboratory chemical	
Supplier	NCL of Wisconsin, Inc.	PO Box 8, Birnamwood, WI 54414
	Telephone: 1-800-648-7836	Fax: 715-449-2454
	Email: nclabs@nclabs.com	Emergency Contact: 1-800-424-9300 (Chemtrec)

SECTION 2: HAZARDS IDENTIFICATION

GHS Classification

Flammable Liquids	Category 3
Specific Target Organ Toxicity	Single Exposure Category 1



Signal Word Danger

Hazard Statements

H226	Flammable liquid and vapor.
H370	Causes damage to organs.

Precautionary Statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P260	Do not breathe mist/vapors/spray.
P264	Wash exposed skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P308+P311	IF exposed or concerned: Call a POISON CENTER or doctor.
P370+P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to comply with local, state and federal regulations.

Other Hazards Not Contributing to the Classification

None under normal conditions.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Identity	Not applicable
Common Name	Not applicable

Mixture

Name	CAS #	Approximate %
Ethyl Alcohol	64-17-5	55.2
Water	7732-18-5	39.7
Sudan Black B	4197-25-5	0.3
Denaturants Present in Ethyl Alcohol		
Methanol	67-56-1	3.0
Ethyl Acetate	141-78-6	0.6
4-Methyl-2-Pentanone	108-10-1	0.6
Aliphatic Hydrocarbons	Unknown	0.6

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General First Aid Measures	Never give anything by mouth to an unconscious person. Seek medical advice if you feel unwell.
If Inhaled	Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor if you feel unwell.
In Case of Skin Contact	Remove all contaminated clothing. Rinse skin with water/shower. Immediately call a POISON CENTER or doctor if you feel unwell.
In Case of Eye Contact	Rinse carefully with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor if you feel unwell.
If Swallowed	Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor if you feel unwell. Ingestion of large quantities: Immediately take to the hospital.

Most Important Symptoms/Effects Acute and Delayed

No additional information.

Indication of Immediate Medical Attention and Special Treatment Needed

Seek medical attention if exposed.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media	Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable Extinguishing Media	Do not use a heavy water stream.
Special Hazards Arising from the Substance or Mixture	Highly flammable. Gas/vapor flammable with air within explosion limits. May be ignited by sparks. Gas/vapors spreads at floor level.
Reactivity	Upon combustion: CO and CO ₂ are formed. Reacts violently with many compounds; strong oxidizers. Violent to explosive reaction with some acids.
Special Protective Equipment and Precautions for Fire-Fighters	Wear self-contained breathing apparatus and protective clothing. Cool tanks/drums with water spray/remove them to safety. Do not move the load if exposed to heat.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions	Use personal protective equipment (see section 8). Evacuate area of non-essential personnel. Eliminate ignition sources.
Environmental Precautions	Prevent entry to sewers and public waters. Keep upwind. Mark the danger area. Consider evacuation. Seal off low-lying areas. Close doors and windows of adjacent premises. Stop engines and no smoking. No naked flames or sparks. Spark and explosion proof appliances and lighting equipment. Keep containers closed. Wash contaminated clothing before reuse.
Methods and Materials for Containment and Cleaning Up	Collect spillage with inert absorbent material. Store away from other materials. Wash clothing/equipment after handling. Ensure compliance with local, state and federal regulations.

SECTION 7: HANDLING AND STORAGE

Handling and Storage

Precautions for Safe Handling

Avoid contact with eyes and skin. Avoid breathing vapors. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.

**Conditions for Safe Storage
Including any Incompatibilities**

Keep in original container tightly closed, stored in a cool, dry, ventilated area. Store away from sunlight, which can contribute to instability. Store away from: heat sources, ignition sources, oxidizing agents, strong acids, water and moisture. Fireproof storeroom. Meet legal requirements.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Ethyl Alcohol, Denatured, Absolute (64-17-5)		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1900 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

Appropriate Engineering Controls

Material should be handled or transferred in a fume hood or with equivalent ventilation. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide adequate general and local exhaust ventilation.

Individual Protection Measures

Avoid all unnecessary exposure.

Skin Protection

Protective gloves and additional protection including impervious boots, apron, or coveralls, as needed in areas of unusual exposure to prevent skin contact.

Eye Protection

Use chemical safety goggles and/or a full face shield where splashing is possible. Contact lenses should not be worn when working with this material. Maintain eye-wash fountain and quick-drench facilities in work area.

Respiratory Protection

Wear appropriate mask.

Other Information

Do not eat, drink or smoke during use.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid
Color	Black
Odor	Slight alcohol odor
Odor Threshold	Not determined
pH	Not determined
Melting Point/Freezing Point	Not determined
Initial Boiling Point and Boiling Range	Not determined
Flash Point	Not determined
Evaporation Rate	Not determined
Flammability (Solid, Gas)	Not determined
Upper/Lower Flammability/Explosive Limits	Not determined
Vapor Pressure	Not determined
Vapor Density	Not determined
Relative Density	0.95
Density	Not determined
Solubility	Soluble in water
Partition Coefficient: n-octanol/water	Not determined
Auto-Ignition Temperature	Not determined
Decomposition Temperature	Not determined
Viscosity	Not determined

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Upon combustion: CO and CO ₂ are formed. Reacts violently with many compounds. Strong oxidizers: increased risk of fire/explosion. Violent explosive reaction with some acids.
Chemical Stability	Stable under ordinary conditions of use and storage.
Possibility of Hazardous Reactions	No data available
Conditions to Avoid	Extremely high or low temperatures. Heat and sunlight can contribute to instability. Open flame.
Incompatible Materials	Strong acids, strong bases, and strong oxidizers
Hazardous Decomposition Products	When heated to decomposition, can emit toxic gases, carbon dioxide, and carbon monoxide. May release flammable gases.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute Toxicity	Not classified
Ethyl Alcohol, Denatured, Absolute (64-17-5)	
LD50 oral rat	10740 mg/kg
LD50 dermal rabbit	>16000 mg/kg
Sudan Black B (4197-25-5)	
LD50 ivn-mus	63 mg/kg
Skin Corrosion/Irritation	Not classified
Serious Eye Damage/Irritation	Not classified
Respiratory or Skin Sensitization	Not classified
Germ Cell Mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive Toxicity	Not classified
Specific Target Organ Toxicity (Single Exposure)	Causes damage to optic nerve.
Specific Target Organ Toxicity (Repeated Exposure)	Not classified
Aspiration Hazard	Not classified
Potential Adverse Human Health Effects and Symptoms	Not additional information.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity	Not applicable
Persistence and Degradability	Not applicable
Bioaccumulative Potential	Not applicable
Mobility in Soil	Not applicable
Other Adverse Effects	Not applicable

SECTION 13: DISPOSAL CONSIDERATIONS

Methods of Disposal

Disposal Recommendations	Dispose of contents/containers in accordance with local, state and federal regulations.
Ecology-Waste Materials	Avoid release to the surrounding environment.

SECTION 14: TRANSPORT INFORMATION

UN Number	1993
UN Shipping Name	Flammable liquids, N.O.S. (contains Ethanol)
Transport Hazard Class(es)	Not applicable

Packing Group	Not applicable
Environmental Hazards	Not applicable
Transport in Bulk	Not applicable
Special Precautions	Not applicable

SECTION 15: REGULATORY INFORMATION


Ethyl Alcohol (64-17-5)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Sudan Black B (4197-25-5)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Water (7732-18-5)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

SECTION 16: OTHER INFORMATION

Revision Date: 04/16/2015

NFPA Hazards

Health Hazard	1: Exposure would cause irritation with only minor residual injury.
Fire Hazard	3: Liquids and solids (including finely divided solids) that can be ignited under almost all ambient temperature conditions.
Reactivity/Instability	0: Normally stable, even under fire exposure conditions, and is not reactive with water.



HMIS III Rating

Health	1: Irritation or minor reversible injury possible.
Flammability	3: Materials capable of ignition under almost all normal temperature conditions.
Physical Hazard	0: Materials that are normally stable, even under fire conditions.
Personal Protection	C

S-99X	
Health	1
Flammability	3
Physical Hazard	0
Personal Protection	C

The information contained herein is provided in good faith and is believed to be correct as of the date hereof. However, NCL of Wisconsin, Inc. makes no representation as to the comprehensiveness or accuracy of the information. It is expected that individuals receiving the information will exercise their independent judgment in determining its appropriateness for their conditions of use. Accordingly, NCL of Wisconsin, Inc. will not be responsible for damages of any kind resulting from the use of or reliance upon such information.

END OF SAFETY DATA SHEET